•	101, 21,0 <u>41,1</u>	
		25X1



PHOTOGRAPHIC INTERPRETATION REPORT

NATIONAL PHOTOGRAPHIC INTERPRETATION CENTER

LIU-CHUNG NAVAL RESEARCH AND DEVELOPMENT FACILITY FU-HSIEN, CHINA

TOP SECRET

25X1

25X1

AUGUST 1974 COPY NO. 122 13 PAGES PIR-050/74



ABSTRACT 1. Liu-chung Naval Research and Development Facility Fu-haien is on a lake near Kun-ming in Yannan Province, China, at 24-35-30N 102-50-35E 1. It is probably engaged in torpedo testing and other types of research and development (R&D) activity. The facility consists of six areas: a berthing facility, an R&D activity, an R&D act, a torpedo test facility, a housing/support area, and two small mooring facilities. A large catamaran and four special-purpose barges at the facility are probably used in R&D activity. 2. This report is based primarily 3. Liu-chung Naval R&D Facility is at the northwestern edge of Fu-hsien Lake, 30 nautical miles (nm) south of Kun-ming (Figure 1). The lake is approximately 15 nm long and is surrounded by high bluffs which isolate the facility. A single road connects the installation with the cities of Kun-ming and Chengchiang. Although several villages are situated along the shore of the lake, very little civilian activity, such as fishing, has been observed. 4. Construction of the facility began between January and August 1967 and it was probably operational by March 1970. Most of the vessels seen at the berthing facility were apparently constructed there. What was probably the catamaran, the largest wessel on the lake, was under constructed there. What was probably the catamaran, the largest wessel on the lake, was under constructed there. What was probably the catamaran the largest vessel on the lake, was under constructed there. What was probably the catamaran to largest reseal on the lake, was under constructed there. What was probably the catamaran to largest reseal on the lake, was under constructed there. What was probably the catamaran to largest reseal on the lake, was under constructed there. What was probably the catamaran to largest reseal on the lake, was under constructed there. What was probably the catamaran to largest reseal on the lake, was under construction at the berthing facility and proper there berthing facility to make the facility of the construct	1. Liu-chung Naval Research and Development Facility Fu-hsien is on a lake near Kun-ming in Yunnan Province, China, at 24-35-30N 102-50-35E			
in Yunnan Province, China, at 24:35:30N 102-50-35E	n Yunnan Province, China, at 24-35-30N 102-50-35E		ABSTRACT	
a detailed description and photographs of each area, pertinent dimensions, and drawings of several special purpose barges observed at the berthing facility. INTRODUCTION 3. Liu-chung Naval R&D Facility is at the northwestern edge of Fu-hsien Lake, 30 nautical miles (mm) south of Kun-ming (Figure 1). The lake is approximately 15 nm long and is surrounded by high bluffs which isolate the facility. A single road connects the installation with the cities of Kun-ming and Cheng-chiang. Although several villages are situated along the shore of the lake, very little civilian activity, such as fishing, has been observed. 4. Construction of the facility began between January and August 1967 and it was probably operational by March 1970. Most of the vessels seen at the berthing facility were apparently constructed there. What was probably the catamaran, the largest vessel on the lake, was under constructed at the berthing facility in March 1970. 5. One area of the installation has been identified as a torpedo test facility similar to the one at Morris Dam, California. This area contains a long ramp inclined along a steep hill. 6. Other specific programs of the facility cannot be identified, but it is likely they involve underwater or submersible activity. Several of the vessels observed on the lake could be used to support an SLBM pop-up test program similar to that at the US facility at San Clemente. 7. Very little movement of the vessels on Fu-hsien Lake has been observed, possibly indicating that the facility is not yet fully operational. The movements of specific vessels have been described in this report where they might indicate special functions. BASIC DESCRIPTION 8. Four of the six areas comprising the installation are concentrated in an area approximately 8,000 feet long at the northwestern edge of Fu-hsien Lake (Figure 2). These areas are the berthing facility, and the housing/support area. The two small mooring facilities are at the northern and southern ends of the lake. Berthing Facility 9. The ber	detailed description and photographs of each area, pertinent dimensions, and drawings of several pecial purpose barges observed at the berthing facility. INTRODUCTION 3. Liu-chung Naval R&D Facility is at the northwestern edge of Fu-hsien Lake, 30 nautical nules (nm) south of Kun-ming (Figure 1). The lake is approximately 15 nm long and is surrounded by high bluffs which isolate the facility. A single road connects the installation with the cities of Kun-ming and Cheng-chiang. Although several villages are situated along the shore of the lake, very sittle civilian activity, such as fishing, has been observed. 4. Construction of the facility began between January and August 1967 and it was probably operational by March 1970. Most of the vessels seen at the berthing facility were apparently onstructed there. What was probably the catamaran, the largest vessel on the lake, was under construction at the berthing facility in March 1970. 5. One area of the installation has been identified as a torpedo test facility similar to the one at Morris Dam, California. This area contains a long ramp inclined along a steep hill. 6. Other specific programs of the facility cannot be identified, but it is likely they involve underwater or submersible activity. Several of the vessels observed on the lake could be used to upport an SLBM pop-up test program similar to that at the US facility at San Clemente.¹ 7. Very little movement of the vessels on Fu-hsien Lake has been observed, possibly indicating hat the facility is not yet fully operational. The movements of specific vessels have been described in this report where they might indicate special functions. BASIC DESCRIPTION 8. Four of the six areas comprising the installation are concentrated in an area approximately 3,000 feet long at the northwestern edge of Fu-hsien Lake (Figure 2). These areas are the berthing acility, the R&D area, the torpedo test facility, and the housing/support area. The two small mooring acilities are at the northwestern edge of Fu-hsien Lake (in Yunnan Province, C torpedo testing and otl of six areas: a berthing two small mooring fact	nina, at 24-35-30N 102-50-35E It is probably ther types of research and development (R&D) activity. The facility facility, an R&D area, a torpedo test facility, a housing/suppor lities. A large catamaran and four special-purpose barges at the	engaged in ty consists t area, and
3. Liu-chung Naval R&D Facility is at the northwestern edge of Fu-hsien Lake, 30 nautical miles (nm) south of Kun-ming (Figure 1). The lake is approximately 15 nm long and is surrounded by high bluffs which isolate the facility. A single road connects the installation with the cities of Kun-ming and Cheng-chiang. Although several villages are situated along the shore of the lake, very little civilian activity, such as fishing, has been observed. 4. Construction of the facility began between January and August 1967 and it was probably operational by March 1970. Most of the vessels seen at the berthing facility were apparently constructed there. What was probably the catamaran, the largest vessel on the lake, was under construction at the berthing facility in March 1970. 5. One area of the installation has been identified as a torpedo test facility similar to the one at Morris Dam, California. This area contains a long ramp inclined along a steep hill. 6. Other specific programs of the facility cannot be identified, but it is likely they involve underwater or submersible activity. Several of the vessels observed on the lake could be used to support an SLBM pop-up test program similar to that at the US facility at San Clemente. In the state of the constant of the vessels of specific vessels have been described in this report where they might indicate special functions. BASIC DESCRIPTION 8. Four of the six areas comprising the installation are concentrated in an area approximately 3,000 feet long at the northwestern edge of Fu-hsien Lake (Figure 2). These areas are the berthing facility, the R&D area, the torpedo test facility, and the housing/support area. The two small mooring facilities are at the northern and southern ends of the lake. Berthing Facility 9. The berthing facility consists of two quays appears and the second was being built in September 1969. Both quays were complete by March 1970. The pier was under construction in July 1972 and complete by November 1972. The facility is secured by a fence	3. Liu-chung Naval R&D Facility is at the northwestern edge of Fu-hsien Lake, 30 nautical niles (nm) south of Kun-ming (Figure 1). The lake is approximately 15 nm long and is surrounded by high bluffs which isolate the facility. A single road connects the installation with the cities of Kun-ming and Cheng-chiang. Although several villages are situated along the shore of the lake, very title civilian activity, such as fishing, has been observed. 4. Construction of the facility began between January and August 1967 and it was probably operational by March 1970. Most of the vessels seen at the berthing facility were apparently constructed there. What was probably the catamaran, the largest vessel on the lake, was under construction at the berthing facility in March 1970. 5. One area of the installation has been identified as a torpedo test facility similar to the one at Morris Dam, California. This area contains a long ramp inclined along a steep hill. 6. Other specific programs of the facility cannot be identified, but it is likely they involve underwater or submersible activity. Several of the vessels observed on the lake could be used to upport an SLBM pop-up test program similar to that at the US facility at San Clemente.\(^1\) 7. Very little movement of the vessels on Fu-hsien Lake has been observed, possibly indicating that the facility is not yet fully operational. The movements of specific vessels have been described in this report where they might indicate special functions. BASIC DESCRIPTION 8. Four of the six areas comprising the installation are concentrated in an area approximately 3,000 feet long at the northwestern edge of Fu-hsien Lake (Figure 2). These areas are the berthing acility, the R&D area, the torpedo test facility, and the housing/support area. The two small mooring acilities are at the northern and southern ends of the lake. 8. Four of the six areas comprising built in September 1969. Both quays were complete by March 1970. The pier was under construction in July 1972 and complete	a detailed description a	nd photographs of each area, pertinent dimensions, and drawings	
miles (nm) south of Kun-ming (Figure 1). The lake is approximately 15 nm long and is surrounded by high bluffs which isolate the facility. A single road connects the installation with the cities of Kun-ming and Cheng-chiang. Although several villages are situated along the shore of the lake, very little civilian activity, such as fishing, has been observed. 4. Construction of the facility began between January and August 1967 and it was probably operational by March 1970. Most of the vessels seen at the berthing facility were apparently constructed there. What was probably the catamaran, the largest vessel on the lake, was under construction at the berthing facility in March 1970. 5. One area of the installation has been identified as a torpedo test facility similar to the one at Morris Dam, California. This area contains a long ramp inclined along a steep hill. 6. Other specific programs of the facility cannot be identified, but it is likely they involve underwater or submersible activity. Several of the vessels observed on the lake could be used to support an SLBM pop-up test program similar to that at the US facility at San Clemente.\(^1\) 7. Very little movement of the vessels on Fu-hsien Lake has been observed, possibly indicating that the facility is not yet fully operational. The movements of specific vessels have been described in this report where they might indicate special functions. BASIC DESCRIPTION 8. Four of the six areas comprising the installation are concentrated in an area approximately 8,000 feet long at the northwestern edge of Fu-hsien Lake (Figure 2). These areas are the berthing facility, the R&D area, the torpedo test facility, and the housing/support area. The two small mooring facility, the R&D area, the torpedo test facility, and the housing/support area. The two small mooring facility he R&D area, the torpedo test facility (Figure 3). One quay was under construction in August 1967 and the second was being built in September 1969. Both quays were complete by March 1970. The pie	niles (nm) south of Kun-ming (Figure 1). The lake is approximately 15 nm long and is surrounded by high bluffs which isolate the facility. A single road connects the installation with the cities of cun-ming and Cheng-chiang. Although several villages are situated along the shore of the lake, very ittle civilian activity, such as fishing, has been observed. 4. Construction of the facility began between January and August 1967 and it was probably operational by March 1970. Most of the vessels seen at the berthing facility were apparently onstructed there. What was probably the catamaran, the largest vessel on the lake, was under construction at the berthing facility in March 1970. 5. One area of the installation has been identified as a torpedo test facility similar to the one at Morris Dam, California. This area contains a long ramp inclined along a steep hill. 6. Other specific programs of the facility cannot be identified, but it is likely they involve underwater or submersible activity. Several of the vessels observed on the lake could be used to upport an SLBM pop-up test program similar to that at the US facility at San Clemente.\(^1\) 7. Very little movement of the vessels on Fu-hsien Lake has been observed, possibly indicating hat the facility is not yet fully operational. The movements of specific vessels have been described in this report where they might indicate special functions. BASIC DESCRIPTION 8. Four of the six areas comprising the installation are concentrated in an area approximately 3,000 feet long at the northwestern edge of Fu-hsien Lake (Figure 2). These areas are the berthing facility, the R&D area, the torpedo test facility, and the housing/support area. The two small mooring actilities are at the northwestern edge of Fu-hsien Lake (Figure 2). These areas are the berthing facility on the per was under construction in laugust 1967 and the second was being built in September 1969. Both quays were complete by March 1970. The pier was under construction in July 1972 and complete by Nov		INTRODUCTION	
operational by March 1970. Most of the vessels seen at the berthing facility were apparently constructed there. What was probably the catamaran, the largest vessel on the lake, was under construction at the berthing facility in March 1970. 5. One area of the installation has been identified as a torpedo test facility similar to the one at Morris Dam, California. This area contains a long ramp inclined along a steep hill. 6. Other specific programs of the facility cannot be identified, but it is likely they involve underwater or submersible activity. Several of the vessels observed on the lake could be used to support an SLBM pop-up test program similar to that at the US facility at San Clemente.\(^1\) 7. Very little movement of the vessels on Fu-hsien Lake has been observed, possibly indicating that the facility is not yet fully operational. The movements of specific vessels have been described in this report where they might indicate special functions. BASIC DESCRIPTION 8. Four of the six areas comprising the installation are concentrated in an area approximately 8,000 feet long at the northwestern edge of Fu-hsien Lake (Figure 2). These areas are the berthing facility, the R&D area, the torpedo test facility, and the housing/support area. The two small mooring facilities are at the northern and southern ends of the lake. Berthing Facility 9. The berthing facility consists of two quays three building/repairways, and a support facility (Figure 3). One quay was under construction in August 1967 and the second was being built in September 1969. Both quays were complete by March 1970. The pier was under construction in July 1972 and complete by November 1972. The facility is secured by a fence. 10. The three building/repairways are on the southeast side of the berthing facility and were present on photography of December 1968. Most of the vessels observed at the facility were probably constructed on these building/repairways. The largest of the vessels, the 145-foot catamaran, was	perational by March 1970. Most of the vessels seen at the berthing facility were apparently constructed there. What was probably the catamaran, the largest vessel on the lake, was under construction at the berthing facility in March 1970. 5. One area of the installation has been identified as a torpedo test facility similar to the one at Morris Dam, California. This area contains a long ramp inclined along a steep hill. 6. Other specific programs of the facility cannot be identified, but it is likely they involve underwater or submersible activity. Several of the vessels observed on the lake could be used to upport an SLBM pop-up test program similar to that at the US facility at San Clemente.\(^1\) 7. Very little movement of the vessels on Fu-hsien Lake has been observed, possibly indicating hat the facility is not yet fully operational. The movements of specific vessels have been described in this report where they might indicate special functions. BASIC DESCRIPTION 8. Four of the six areas comprising the installation are concentrated in an area approximately acility, the R&D area, the torpedo test facility, and the housing/support area. The two small mooring acilities are at the northern and southern ends of the lake. 3erthing Facility 9. The berthing facility consists of two quays hree building/repairways, and a support facility (Figure 3). One quay was under construction in largust 1967 and the second was being built in September 1969. Both quays were complete by March 1970. The pier was under construction in July 1972 and complete by November 1972. The acility is secured by a fence. 10. The three building/repairways are on the southeast side of the berthing facility and were present on photography of December 1968. Most of the vessels observed at the facility were probably constructed on these building/repairways. The largest of the vessels, the 145-foot catamaran, was	miles (nm) south of Ku by high bluffs which i Kun-ming and Cheng-ch	n-ming (Figure 1). The lake is approximately 15 nm long and is solate the facility. A single road connects the installation with the lang. Although several villages are situated along the shore of the	surrounded ne cities of
6. Other specific programs of the facility cannot be identified, but it is likely they involve underwater or submersible activity. Several of the vessels observed on the lake could be used to support an SLBM pop-up test program similar to that at the US facility at San Clemente.\frac{1}{2} 7. Very little movement of the vessels on Fu-hsien Lake has been observed, possibly indicating that the facility is not yet fully operational. The movements of specific vessels have been described in this report where they might indicate special functions. BASIC DESCRIPTION 8. Four of the six areas comprising the installation are concentrated in an area approximately 8,000 feet long at the northwestern edge of Fu-hsien Lake (Figure 2). These areas are the berthing facility, the R&D area, the torpedo test facility, and the housing/support area. The two small mooring facilities are at the northern and southern ends of the lake. Berthing Facility 9. The berthing facility consists of two quays three building/repairways, and a support facility (Figure 3). One quay was under construction in August 1967 and the second was being built in September 1969. Both quays were complete by March 1970. The pier was under construction in July 1972 and complete by November 1972. The facility is secured by a fence. 10. The three building/repairways are on the southeast side of the berthing facility and were present on photography of December 1968. Most of the vessels observed at the facility were probably constructed on these building/repairways. The largest of the vessels, the 145-foot catamaran, was	6. Other specific programs of the facility cannot be identified, but it is likely they involve underwater or submersible activity. Several of the vessels observed on the lake could be used to upport an SLBM pop-up test program similar to that at the US facility at San Clemente.\frac{1}{2} 7. Very little movement of the vessels on Fu-hsien Lake has been observed, possibly indicating that the facility is not yet fully operational. The movements of specific vessels have been described in this report where they might indicate special functions. BASIC DESCRIPTION 8. Four of the six areas comprising the installation are concentrated in an area approximately acility, the R&D area, the torpedo test facility, and the housing/support area. The two small mooring acilities are at the northern and southern ends of the lake. Berthing Facility 9. The berthing facility consists of two quays here building/repairways, and a support facility (Figure 3). One quay was under construction in hougust 1967 and the second was being built in September 1969. Both quays were complete by March 1970. The pier was under construction in July 1972 and complete by November 1972. The acility is secured by a fence. 10. The three building/repairways are on the southeast side of the berthing facility and were present on photography of December 1968. Most of the vessels observed at the facility were probably constructed on these building/repairways. The largest of the vessels, the 145-foot catamaran, was	operational by March constructed there. Wha	1970. Most of the vessels seen at the berthing facility were t was probably the catamaran, the largest vessel on the lake,	apparently
underwater or submersible activity. Several of the vessels observed on the lake could be used to support an SLBM pop-up test program similar to that at the US facility at San Clemente. 7. Very little movement of the vessels on Fu-hsien Lake has been observed, possibly indicating that the facility is not yet fully operational. The movements of specific vessels have been described in this report where they might indicate special functions. **BASIC DESCRIPTION** 8. Four of the six areas comprising the installation are concentrated in an area approximately 8,000 feet long at the northwestern edge of Fu-hsien Lake (Figure 2). These areas are the berthing facility, the R&D area, the torpedo test facility, and the housing/support area. The two small mooring facilities are at the northern and southern ends of the lake. **Berthing Facility** 9. The berthing facility consists of two quays	anderwater or submersible activity. Several of the vessels observed on the lake could be used to upport an SLBM pop-up test program similar to that at the US facility at San Clemente. 7. Very little movement of the vessels on Fu-hsien Lake has been observed, possibly indicating hat the facility is not yet fully operational. The movements of specific vessels have been described in this report where they might indicate special functions. BASIC DESCRIPTION 8. Four of the six areas comprising the installation are concentrated in an area approximately 3,000 feet long at the northwestern edge of Fu-hsien Lake (Figure 2). These areas are the berthing acility, the R&D area, the torpedo test facility, and the housing/support area. The two small mooring acilities are at the northern and southern ends of the lake. Berthing Facility 9. The berthing facility consists of two quays 9. The berthing facility consists of two quays 10. The pier was under construction in July 1972 and complete by November 1972. The acility is secured by a fence. 10. The three building/repairways are on the southeast side of the berthing facility and were present on photography of December 1968. Most of the vessels observed at the facility were probably constructed on these building/repairways. The largest of the vessels, the 145-foot catamaran, was			
that the facility is not yet fully operational. The movements of specific vessels have been described in this report where they might indicate special functions. BASIC DESCRIPTION 8. Four of the six areas comprising the installation are concentrated in an area approximately 8,000 feet long at the northwestern edge of Fu-hsien Lake (Figure 2). These areas are the berthing facility, the R&D area, the torpedo test facility, and the housing/support area. The two small mooring facilities are at the northern and southern ends of the lake. Berthing Facility 9. The berthing facility consists of two quays 4 pier three building/repairways, and a support facility (Figure 3). One quay was under construction in August 1967 and the second was being built in September 1969. Both quays were complete by March 1970. The pier was under construction in July 1972 and complete by November 1972. The facility is secured by a fence. 10. The three building/repairways are on the southeast side of the berthing facility and were present on photography of December 1968. Most of the vessels observed at the facility were probably constructed on these building/repairways. The largest of the vessels, the 145-foot catamaran, was	hat the facility is not yet fully operational. The movements of specific vessels have been described in this report where they might indicate special functions. BASIC DESCRIPTION 8. Four of the six areas comprising the installation are concentrated in an area approximately 8,000 feet long at the northwestern edge of Fu-hsien Lake (Figure 2). These areas are the berthing acility, the R&D area, the torpedo test facility, and the housing/support area. The two small mooring acilities are at the northern and southern ends of the lake. Berthing Facility 9. The berthing facility consists of two quays hree building/repairways, and a support facility (Figure 3). One quay was under construction in August 1967 and the second was being built in September 1969. Both quays were complete by March 1970. The pier was under construction in July 1972 and complete by November 1972. The acility is secured by a fence. 10. The three building/repairways are on the southeast side of the berthing facility and were present on photography of December 1968. Most of the vessels observed at the facility were probably constructed on these building/repairways. The largest of the vessels, the 145-foot catamaran, was	underwater or submersi	ble activity. Several of the vessels observed on the lake could	be used to
8. Four of the six areas comprising the installation are concentrated in an area approximately 8,000 feet long at the northwestern edge of Fu-hsien Lake (Figure 2). These areas are the berthing facility, the R&D area, the torpedo test facility, and the housing/support area. The two small mooring facilities are at the northern and southern ends of the lake. Berthing Facility 9. The berthing facility consists of two quays	8. Four of the six areas comprising the installation are concentrated in an area approximately 3,000 feet long at the northwestern edge of Fu-hsien Lake (Figure 2). These areas are the berthing acility, the R&D area, the torpedo test facility, and the housing/support area. The two small mooring acilities are at the northern and southern ends of the lake. Berthing Facility 9. The berthing facility consists of two quays	that the facility is not	yet fully operational. The movements of specific vessels have been	
8,000 feet long at the northwestern edge of Fu-hsien Lake (Figure 2). These areas are the berthing facility, the R&D area, the torpedo test facility, and the housing/support area. The two small mooring facilities are at the northern and southern ends of the lake. Berthing Facility 9. The berthing facility consists of two quays three building/repairways, and a support facility (Figure 3). One quay was under construction in August 1967 and the second was being built in September 1969. Both quays were complete by March 1970. The pier was under construction in July 1972 and complete by November 1972. The facility is secured by a fence. 10. The three building/repairways are on the southeast side of the berthing facility and were present on photography of December 1968. Most of the vessels observed at the facility were probably constructed on these building/repairways. The largest of the vessels, the 145-foot catamaran, was	3,000 feet long at the northwestern edge of Fu-hsien Lake (Figure 2). These areas are the berthing facility, the R&D area, the torpedo test facility, and the housing/support area. The two small mooring facilities are at the northern and southern ends of the lake. 3erthing Facility 9. The berthing facility consists of two quays		BASIC DESCRIPTION	
9. The berthing facility consists of two quays	9. The berthing facility consists of two quays	8,000 feet long at the facility, the R&D area,	northwestern edge of Fu-hsien Lake (Figure 2). These areas are the torpedo test facility, and the housing/support area. The two sm	ne berthing
three building/repairways, and a support facility (Figure 3). One quay was under construction in August 1967 and the second was being built in September 1969. Both quays were complete by March 1970. The pier was under construction in July 1972 and complete by November 1972. The facility is secured by a fence. 10. The three building/repairways are on the southeast side of the berthing facility and were present on photography of December 1968. Most of the vessels observed at the facility were probably constructed on these building/repairways. The largest of the vessels, the 145-foot catamaran, was	hree building/repairways, and a support facility (Figure 3). One quay was under construction in August 1967 and the second was being built in September 1969. Both quays were complete by March 1970. The pier was under construction in July 1972 and complete by November 1972. The acility is secured by a fence. 10. The three building/repairways are on the southeast side of the berthing facility and were present on photography of December 1968. Most of the vessels observed at the facility were probably constructed on these building/repairways. The largest of the vessels, the 145-foot catamaran, was	Berthing Facility		
present on photography of December 1968. Most of the vessels observed at the facility were probably constructed on these building/repairways. The largest of the vessels, the 145-foot catamaran, was	present on photography of December 1968. Most of the vessels observed at the facility were probably constructed on these building/repairways. The largest of the vessels, the 145-foot catamaran, was	three building/repairway August 1967 and the s March 1970. The pier v	rs, and a support facility (Figure 3). One quay was under cons econd was being built in September 1969. Both quays were co was under construction in July 1972 and complete by November	omplete by
		present on photography constructed on these b	of December 1968. Most of the vessels observed at the facility wer uilding/repairways. The largest of the vessels, the 145-foot catal	e probably naran, was

25X1

25X1

25X1

25**X**1

25X1

25X1

TOP SECRET RUFF

Sanitized Copy	Approved for Release	2011/07/14 : CIA-RDP78 Seukei kuff	105162A0004	100010035-9		25X
						25X
						25X1
					•	
					4	
					•	
		1 111 (4074 77		
building/repairways a		on one building/repairwa naintenance of the vessel				
	was observed here in D			,		
11. The suppo	rt facility for the berth	ing facility is adjacent t	to the quays a	nd consists of a		
shop building with th	ree stacks, two storage l	ouildings, four support bu	ildings, and a l	basketball court.		
		directly behind one of the motor launch, two smal			•	
a generator, and two		present in February 19			•	
building sections for		ng fabricated on the qua rs and quays in several a				
fashion at the same						
12. Thirteen ve	essels and barges are asso	ociated with the installat	ion and are us	ually seen at the		
berthing facility. Eig	ht of these are support	craft and five are specia	al function ves	sels. The largest		
		measuring 145 by 45 fe 970 and April 1971. A tr				
long with rails	is centered of	over the well formed by	the twin hul	ls of the vessel.		
The rails are supported	ed by two heavy A-frame	es and the rails extend pa		e hulls. Forward (Continued p. 5)		
		- 2 -		,		051
						25 X
	TAN	SECRET RUFF				

Sanitized Copy Approved for Release 2011/07/14 : CIA-RDP78T05162A000400010035-9



of the well, the vessel is fitted with a high bridge spanning the entire beam. The bridge and both decks aft of the bridge appear to be covered by stretched canvas.

13. The catamaran has rarely been observed away from the quay at the berthing facility. In August 1972, the vessel was dead in the water approximately 2,000 feet northeast of the berthing facility and in July 1972 it was mediterranean-moored to the shore near the building/repairways. One of the special purpose barges was in the well of the catamaran in January 1972 and in July 1974 an unidentified object was in the well.

14. Two special-purpose barges and two barge-like objects have also been seen at the berthing facility. The smaller of the two barges (barge A) (Figure 4). It has an inclined way with two probable rails running longitudinally along its center section. A possible winch is aft of the inclined way. A possible pilot house with at least one small mast is at the starboard side and another raised section is at the port side. All of the raised sections appear to be canvas covered. A crane is mounted on the starboard side in front of the possible pilot house and two mooring winches are on either side of the bow.

15. Barge A has been observed at or near the quay at the R&D area 2,000 feet south of the berthing facility. On two occasions, in July and August 1972, the forward section of the inclined way appeared to be covered. In December 1972, a tentlike structure was observed over the forward part of the craft while it was at the berthing facility. The function of this barge cannot be determined from available photography, but its design indicates that it can discharge or retrieve small, but relatively heavy objects, possibly submersible objects.

16. The second special-purpose barge (barge B) and has two raised sections [Figure 5]. A possible open well is between the two sections. Two open towers between the raised sections were added between February and July 1974. A tower, possibly a pilot house, is aft of the two open towers. The top of the tower is canvas covered. An observation deck with a possible small antenna is atop one of the raised sections. A crane is mounted at the end of the barge opposite the towers and mooring winches are at each corner of




FIGURE 4. BARGE A

Sanitized Copy Approved for Release 2011/07/14: CIA-RDP78T05162A000400010035-9

25X1 25X1 25X1 25X1 25X1

25X1 25X1

25X1

25X1

25X1

25X1

25X1

25X1

25X1

25X1

25X1

25X1 25X1 25X1

25X1

25X1

25X1




FIGURE 5. BARGE B

the barge.

the rails in the center of the barge.

17. Barge B has been observed away from the quay at the berthing facility only once. It was near the building/repairways with the catamaran in July 1972.

18. The first of the two barge-like objects (barge C)
It was constructed on the building/repairways between August and December 1972
The structure was canvas covered until January 1974, when the cover had been removed. The interio
of the structure is divided into three equal sections, The structure was probably
still under construction when seen in April 1974.
19. Barge C was seen at the berthing facility through February 1974. In April 1974 it was seen at the quay in the R&D area. A ramp connected the barge with the southeastern end of the quay and the structure was again covered. A permanent roof had been built over the barge by July 1974. This barge may be used as an offshore observation platform.
20. The second barge-like object (barge D) at the berthing facility [(Figure
6). Barge D has two possible rails over what appears to be an open framework. A
short column with a hemispherical cap is between the rails; it projects above

- 21. What was probably barge D was seen in the well of the catamaran in January and February 1972. Since then it has been seen in several positions in the berthing facility. By May 1974 it had been removed from the water and was sitting on the pier.
- 22. Of the eight support craft observed at the facility, two are work barges which are used in construction and maintenance of the facility. One of the barges is a large floating shearlegs crane

 The second work barge is a large floating jib crane

 feet. Other craft seen at the facility are a YU-CHAI-class LCM, a Yulin River patrol craft (PBR),

- 6 -

TOP SECRET RUFF

Sanitized Copy Approved for Release 2011/07/14 : CIA-RDP78T05162A000400010035-9

5X1 5X1

25X1

25X

a small probable transport or ferry, two small probable LCMs, the BMK 150 motor launch, and a powerboat.

R&D Area

- 23. The R&D area, 3,200 feet south of the berthing facility, consists of an operational facility and a housing/support area (Figure 7). The area is served by a single road, part of which is surfaced with concrete. Most of the area is secured by a wall.
- 24. The operational facility consists of two long R&D buildings, one small R&D building, a semirevetted special-purpose building, six adit entrances, two possible adit entrances, three storage bunkers, one small drive-in support building, five support buildings, a quay, and a small instrumentation/observation building.
- 25. Each of the R&D buildings and the special-purpose building have large drive-in entrances. Six small horizontal tanks directly behind the special-purpose building are probably connected to the building by an overhead pipeline.
- 26. Four of the adit entrances near the R&D buildings probably house underground transformers or related equipment. Four powerlines radiate from one of the adits and the area is similar to other hardened transformer yards. One support building near the adits is also probably associated with electric power.
- 27. A large possible adit is in the hill just west of the R&D quay. This adit may be connected by a tunnel to a smaller adit which opens on the quay. Two probable rails, appear to follow the road from the small adit at the quay to a point near the western end of the R&D buildings. A set of rails branches from the main rails to a covered adit entrance. Another set of rails probably branches from the main rails to the southeastern side of the quay.
- 28. The quay and was constructed about the same time as the remainder of the facility. Support craft are often seen at the quay and barge A has been observed near the southeastern end of the quay against the bluff. Mooring pylons have been constructed along the base of the bluff. A small ramp, partially covering the rails, was at the southeastern end of the quay in February 1974. this ramp was attached to barge D, which was observed away from the berthing facility for the first time.

 (Continued p. 9)




FIGURE 6. BARGE D


- 7 -

TOP SECRET RUFF

25X1

25X1

Sanitized Copy Approved for Release 2011/07/14 : CIA-RDP78T05162A000400010035-9



25X1

25X1

25X1 25X1


25X1

25X1

25X1

25X1

TOP SECRET RIIFE



	TOP SECRET RIIFE	25X
		25X
Activity		
and Development Fac of observation/instru	exception of torpedo testing, most of the activity at Liu-chung Naval Research cility remains unidentified. However, the presence of special-purpose vessels and imentation positions that are probably not required for torpedo testing suggests may be taking place here.	
that have been obse of the special-purpor	test or support equipment has been identified at the installation. The only vehicles erved are cargo trucks and truck-mounted cranes. Consequently, the movement use vessels in the facility provides almost the only indicator of activities or test ity of activity suggests that some of the test programs may not be operational.	
A and C, both which barge A was moored part of the inclined transferred from the	rpose vessels observed to have made significant moves within the facility are barges ich have been observed at the R&D quay. Throughout July and August 1972 and near the southeastern end of the quay and at the quay itself. The forward I way was covered by a tent. The tent possibly covered a piece of equipment e R&D quay to barge A and later discharged by its inclined way (Figure 10). barge suggests that the equipment may be submersible.	
	oring buoys in the test area 300 feet east of the quay in August 1972 indicate possibly was in progress at that time (Figure 10).	
	REFERENCES	
		25X
MAPS OR CHARTS	get Chart, Series 200, Sheet M0496-22HL, 2d ed, Feb 68, scale 1:200,000 (SECRET	
ACIC. US AIT Targ		25X
ACIC. US Air Taig		
	otage Chart, Series 500, TPC H11D, 1st ed, Aug 68, scale 1:500,000 (UNCLASSIFIED)	
ACIC. Tactical Pilo	otage Chart, Series 500, TPC H11D, 1st ed, Aug 68, scale 1:500,000 (UNCLASSIFIED) .NB MSG 071957Z, 7 Feb 74 (TOP SECRET RUFF)	
ACIC. Tactical Pilo		
ACIC. Tactical Pilo DOCUMENT 1. CIA. IAS/MD/A		25
ACIC. Tactical Pilo DOCUMENT 1. CIA. IAS/MD/A. REQUIREMENT		25X
ACIC. Tactical Pilo DOCUMENT 1. CIA. IAS/MD/A. REQUIREMENT		25X

Sanitized Copy Approved for Release 2011/07/14 : CIA-RDP78T05162A000400010035-9

TOP SECRET